



SPECIFICATION

Model			DV-3000-MT with C-axis	DV-4000-MT with C-axis
Working table				
Table Diameter	mm (inch)		Ø3000 (118)	Ø4000 (157)
Max. Table Load	kg (lbs)		22000 (48400)	26000 (57200)
Travel				
Z axis Travel	mm (inch)		2300 (91)	1350 (91) / 1500 (59)
X axis Travel	mm (inch)		1200 (47) / 1500 (59)	2800 (110)
W-Axis Travel	mm (inch)		1400 (55)	1700 (67)
Spindle				
Spindle speed	Low	rpm/min	2~32	1~16
	High	rpm/min	33~100	17~60
Spindle Motor		KW	60/75(α60HVi)	100(α100HVi)
Feedrate				
X Axis Feed Rate	mm (inch)/min		8000 (315)	7000 (276)
Z Axis Feed Rate	mm (inch)/min		10000 (394)	10000 (394)
W Axis Moving Rate	mm (inch)/min		600 (24)	600 (24)
Cutting Feed Rate	mm (inch)/rev		1~2100 (83)	1~2100 (83)
ATC Magazine				
Number of Tool	Pcs		16	16
Machine Size				
Machine size	mm (inch)		7935*5156*6559 (312x203x258)	8491*5392*6859 (334x212x270)
Machine Weight	kg (lbs)		58900 (129816)	71800 (158247)

