



SPECIFICATION

Model	LZ-450	LZ-720	LZ-1000	LZ-1300	LZ-1416
X axis mm(inch)	450 (17.7)	720 (28.3)	1000 (39.4)	1300 (51.2)	1400 (55.1)
Y axis mm(inch)	350 (13.8)	500 (19.7)	600 (23.6)	800 (31.5)	1600 (63)
Z axis mm(inch)	300 (11.8)	400 (15.7)	500 (19.7)	600 (23.6)	600 (23.6)
Table size mm(inch)	500 x 400 (19.7x15.7)	750 x 500 (29.5x19.7)	1100 x 550 (43.3x21.7)	1400 x 850 (55.1x33.5)	1500 x 1600 (59x63)
Max. table loading kg(lbs)	200 (440.8)	400 (881.6)	1000 (2204)	2500 (5512.5)	3000 (6612)
Rapid feedrate m(inch)/min	20 (787.4)	30 (1181)	30 (1181)	20 (787.4)	20 (787.4)
Cutting feedrate m(inch)/min	20 (787.4)	20 (787.4)	20 (787.4)	20 (787.4)	20 (787.4)
Max. spindle speed (rpm)	36000 / 50000		10000 / 15000 / 24000 / 36000		
Magazine capacity (pcs)	12 (20)	16	16	20	20
Spindle motor (kw)	6.0/7.8 / 20/26	11/14.7 / 20/25	11 / 30/39	11 / 30/39	22
Machine weight (kgs)	5500 (12122)	6040 (13312)	8600 (18954)	15210 (33523)	24500 (53998)



©1993-2014 All rights reserved. Lymco, Lywentech, Co. Ltd.