



SPECIFICATION			
Model	MH-500	MH-500E	MH-500P
Travel			
X axis mm(inch)	610 (24)	800 (31)	800 (31)
Y axis mm(inch)	510 (21)	650 (26)	650 (26)
Z axis mm(inch)	610 (24)	800	800 (31)
Pallet			
Pallet working area mm(inch)	500x500 (20x20)	500x500 (20x20)	500x500 (20x20)
Pallet change time (sec)	7~8	7~8	6.8
Max. loading capacity kg (lbs)	450 (990)	500 (1100)	500 (1100)
Spindle			
Taper	ISO No. 40	BT 50	BT 50
Spindle motor (kw)	11/15	11/15	11/15
speed (rpm)	10000 (15000)	10000 (15000)	10000 (15000)
Feed Rate			
Rapid speed X, Y ,Z mm(inch)/min	32000 (1260)	48000 (1890)	60000 (2362)
Cutting feed mm(inch)/min	1~8000 (3150)	1~8000 (3150)	1~8000 (3150)
Tool			
Tool capacity (pcs)	40 (60)	40 (60/120/180)	40 (60/120/180)
Machine Size			
Machine height mm(inch)	3890 (153)	2715 (107)	2715 (107)
Floor space mm(inch)	3380x2603 (133x102)	7200x5050 (283x199)	7200x5050 (283x199)
Machine weight (w/o ATC) kgs (lbs)	9230 (20306)	15350 (33770)	15350 (33770)

() optional specification

Specifications are subject to change without notice

● ●

