

INDUSTRIAL SYSTEMS AND EQUIPMENT DESIGNED, BUILT AND DELIVERED WITH AN INNOVATIVE VISION





AUTOMATION



SPECIAL EQUIPMENT



LINE FOR CIRCULAR SAW TUBE CUTTING





NG-TECH SRL

Via Luigi Dalla Via, 15 36015 SCHIO (VI) ITALY

Tel. +39.0445.57.67.37 info@ng-tech.it

ng-tech.it



CICLOMAX1500

PERFORMANCES

Round section: max Ø 100 mm **Square section:** max □80 x 80 mm **Rectangular section:** max 100 x 70 mm

Solid section: max Ø 60 mm

Cut: Straight

FUNCTIONALITY

Blade type: HSS - TCT

Piece length setting: From the touch screen CN in-feeding gripper by Servo motor

Trim cut: Settable from the touch screen **Sorting:** Settable from the touch screen

Production statistics: Displayed on the touch screen

Tele assistance: Ethernet cable

Industry 4.0 function: Installed on connected PC

Clampin System: Adjustable in strenght by adjusting the oil pressure

CONFIGURATION

Blade diameter: Ø 285 ÷ 350 mm Blade motor: 4 kW (7kW option)

Blade lubrification: Emulsion or micro lubrication

Movement of the cutting head: Recirculating ball screw with brushless motor

Bars feeding: Gripper with Servo motor

Control: PLC

Operator interface: Touch-screen HMI

OPTIONS

Automatic bundle loader "BM"

Deburring machine

End-Working machine: Chamfering mach. and Boring mach

Steel head: Blade motor 11kW for cutting solid bars

Customized unloading system: Conveyor belt that manages the unloading on

NG-tech

three or more sides plus front positions (scraps) Simultaneous cutting of multiple tubes: 2 pcs - 4 pcs

NG-techi





CICLOMAX1500









